

尺寸图

插针参数表

**M40 铆压插针**

材料：铜镀金

接触直径：φ3.6

接触直径：φ2

**M923 铆压式公针**

线规
1.0-2.5mm <sup>2</sup>
2.5-4.0mm <sup>2</sup>
4.0-6.0mm <sup>2</sup>
6.0-10.0mm <sup>2</sup>

**M923 铆压式母针**

线规
0.25-1.0mm <sup>2</sup>
0.75-1.5mm <sup>2</sup>
1.0-2.5mm <sup>2</sup>
4.0-4.0mm <sup>2</sup>

接线定义

芯位	线芯颜色		导体规格
	2+3+PE芯		
U	BK	■	3.6mm <sup>2</sup>
V	BK	■	3.6mm <sup>2</sup>
W	BK	■	3.6mm <sup>2</sup>
PE ⊥	GNYE	■ ■	3.6mm <sup>2</sup>
+	BK	■	2.0mm <sup>2</sup>
-	WH	■	2.0mm <sup>2</sup>

芯位	线芯颜色		导体规格
	4+3+PE芯		
U	BK	■	3.6mm <sup>2</sup>
V	BK	■	3.6mm <sup>2</sup>
W	BK	■	3.6mm <sup>2</sup>
PE ⊥	GNYE	■ ■	3.6mm <sup>2</sup>
+	BK	■	2.0mm <sup>2</sup>
-	BK	■	2.0mm <sup>2</sup>
1	BK	■	2.0mm <sup>2</sup>
2	BK	■	2.0mm <sup>2</sup>

电气参数

芯数	针型	额定电流	额定电压		导体规格	孔型
			A/C	D/C	mm <sup>2</sup>	
2+3+PE		70A/30A	630V	250V	3.6/2	
4+3+PE		70A/30A	630V	250V	3.6/2	