



PM2.5N

安规认证  		
规格	UL	IEC
额定电压	300V	500V
额定电流	20A	24A
单芯线(AWG/mm ²)	22~12 / 0.34~4	
多芯线(AWG/mm ²)	22~12 / 0.34~2.5	
冲击耐压	6KV	
扭力(N-m)	0.39	
螺丝	M2.5	
剥线长度	6~8mm	
绝缘材料	PA	
TxHxW(mm)	5.1x20x22	
包装量	100	

PM4N

安规认证  		
规格	UL	IEC
额定电压	300V	500V
额定电流	30A	32A
单芯线(AWG/mm ²)	22~10 / 0.5~6	
多芯线(AWG/mm ²)	22~10 / 0.5~4	
冲击耐压	6KV	
扭力(N-m)	0.49	
螺丝	M3	
剥线长度	6~8mm	
绝缘材料	PA	
TxHxW(mm)	6.1x23x22	
包装量	100	

PM6N

安规认证  		
规格	UL	IEC
额定电压	300V	500V
额定电流	65A	41A
单芯线(AWG/mm ²)	20~6 / 0.5~10	
多芯线(AWG/mm ²)	20~6 / 0.5~6	
冲击耐压	6KV	
扭力(N-m)	1.18	
螺丝	M4	
剥线长度	9~11mm	
绝缘材料	PA	
TxHxW(mm)	8x29.8x30	
包装量	100	

