




- 产品类型：PCB端子,
- 接线方式：弹簧连接,
- 间距：2.54mm,
- 电压：150V,
- 电流：6A,
- 位数：2-24P
- 认证：UL(Applying) VDE(Applying)

基本参数


间距(Pitch):	2.54mm
电压(Rated voltage)-UL:	150V
电流(Rated current)-UL:	6A
电压(Rated voltage)-IEC:	160V
电流(Rated current)-IEC:	8A
线径(Wire range)-UL:	30-18AWG
线径(Wire range)-IEC:	1.0mm ²
位数(Pole number):	02~24P
认证(Approval):	UL(Applying) , VDE(Applying)



SA254-11



SM254-00



SM254-00R

间距(Pitch):	2.54mm	
标准(Standard):	UL	IEC
电压(Rated voltage):	150V	160V
电流(Rated current):	6A	8A
线径(Wire range):	30-18AWG	1.0mm ²
位数(Pole number):	02~24P	
认证(Approval)		
UL(Applying) VDE(Applying)		

间距(Pitch):	2.54mm	
标准(Standard):	UL	IEC
电压(Rated voltage):	150V	130V
电流(Rated current):	2A	-
线径(Wire range):	26-20AWG	1.0mm ²
位数(Pole number):	02~24P	
认证(Approval)		
 		

间距(Pitch):	2.54mm	
标准(Standard):	UL	IEC
电压(Rated voltage):	150V	130V
电流(Rated current):	2A	-
线径(Wire range):	26-20AWG	1.0mm ²
位数(Pole number):	02~24P	
认证(Approval)		
 		



SM250-C
SM500-C



SM250-D
SM500-D

间距(Pitch):	2.50mm(5.00mm)	
标准(Standard):	UL	IEC
电压(Rated voltage):	250V	250V
电流(Rated current):	2A	2A
线径(Wire range):	20AWG	0.2-0.5mm ²
位数(Pole number):	02~24P	
认证(Approval)		
  		

间距(Pitch):	2.50mm(5.00mm)	
标准(Standard):	UL	IEC
电压(Rated voltage):	250V	250V
电流(Rated current):	2A	2A
线径(Wire range):	20AWG	0.2-0.5mm ²
位数(Pole number):	02~24P	
认证(Approval)		
  		

订购产品

产品名称	间距	位数	产品型号	3D下载	2D下载
固定式端子	2.54mm	02~24P	SA254-11		

资料下载

产品目录	接线端子选型手册
------	--------------------------