




- 产品类型：PCB端子,
- 接线方式：弹簧连接,
- 间距：5.00mm(5.08mm),
- 电压：300V,
- 电流：20A,
- 位数：2-24P

基本参数

|                                                     |                                                                     |
|-----------------------------------------------------|---------------------------------------------------------------------|
| 间距(Pitch):                                          | 5.00mm(5.08mm)                                                      |
| 电压(Rated voltage)-UL:                               | 300V                                                                |
| 电流(Rated current)-UL:                               | 20A                                                                 |
| 电压(Rated voltage)-IEC:                              | 300V                                                                |
| 电流(Rated current)-IEC:                              | 20A                                                                 |
| 线径(Wire range)-UL:                                  | 26-14AWG                                                            |
| 线径(Wire range)-IEC:                                 | 0.34-4mm <sup>2</sup>                                               |
| 位数(Pole number):                                    | 02~24P                                                              |
| 绝缘材料(Insulation Material):                          | PA66 UL94 V-0                                                       |
| 电流承载部件材料和镀层(Material & Plating of Current carrier): | Copper alloy, Tin plated                                            |
| 绝缘电阻(Insulation Resistance):                        | 500MΩ or more at DC500V                                             |
| 耐电压(1分钟)(Withstanding Voltage/1Min):                | 2200V                                                               |
| 额定冲击电压(Rated surge voltage):                        | -                                                                   |
| 接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.):     | M2.5, 0.4Nm Max                                                     |
| 接线弹片材料(Material of Clamp spring):                   | -                                                                   |
| 剥线长度(Wire stripping length):                        | 6.0mm                                                               |
| 使用温度(Operating temperature):                        | -40℃ ~ +105℃                                                        |
| 焊接方式(Soldering recommend):                          | Wave soldering, 260℃ 5S Max(Single Wave), 260℃ 10S Max(Double Wave) |
| 认证(Approval):                                       |                                                                     |

尺寸图



订购产品

| 产品名称  | 间距     | 位数     | 产品型号     | 3D下载 | 2D下载 |
|-------|--------|--------|----------|------|------|
| 固定式端子 | 5.00mm | 02~24P | SA500-12 |      |      |
| 固定式端子 | 5.08mm | 02~24P | SA508-12 |      |      |

资料下载

|      |                          |
|------|--------------------------|
| 产品目录 | <a href="#">接线端子选型手册</a> |
|------|--------------------------|