




- 产品类型：插拔式端子,
- 接线方式：弹簧连接,
- 间距：5.00mm(5.08mm),
- 电压：300V,
- 电流：16A,
- 位数：2-24P

## 基本参数

间距(Pitch):	5.00mm(5.08mm)
电压(Rated voltage)-UL:	300V
电流(Rated current)-UL:	16A
电压(Rated voltage)-IEC:	320V
电流(Rated current)-IEC:	20A
线径(Wire range)-UL:	30-12AWG
线径(Wire range)-IEC:	0.2-2.5mm <sup>2</sup> sol/str 4mm <sup>2</sup> sol
位数(Pole number):	02~24P
绝缘材料(Insulation Material):	PA66 UL94 V-0
电流承载部件材料和镀层(Material & Plating of Current carrier):	Copper alloy, Tin plated
绝缘电阻(Insulation Resistance):	500MΩ or more at DC500V
耐电压(1分钟)(Withstanding Voltage/1Min):	2200V
额定冲击电压(Rated surge voltage):	4000V
接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.):	M3, 0.5~0.7N·m
固定螺丝(Mounting Screw), 扭矩(torque):	-
接线弹片材料(Material of Clamp spring):	-
剥线长度(Wire stripping length):	6.5 ~ 7.5mm
使用温度(Operating temperature):	-40°C ~ +115°C(UL) / -40°C ~ +120°C(IEC)
焊接方式(Soldering recommend):	-
认证(Approval):	

尺寸图



订购产品

产品名称	间距	位数	产品型号	3D下载	2D下载
插拔式端子	5.00mm	02~24P	SPA500-00R		
插拔式端子	5.08mm	02~24P	SPA508-00R		

资料下载

产品目录	<a href="#">接线端子选型手册</a>
------	--------------------------